










AC Drives	Variable Speed Drive		
	 ERCFW08	 ERCFW09	 ERCFW10
Features			
Power Rating	0.18-15kW/0.25-20HP	0.1-1100kW/1.5-1500HP	0.18-2.2kW/1.5-3.0HP
Supply Voltage	200-240V 1-Phase and 3-Phase 380-480V 3-Phase	220-690V	110-240V
Display	Integral/Remote	Integral/Detachable	Integral
Phases	1-Phase or 3-Phase	3-Phase	1-Phase
Control Mode	V/Hz/Sensorless/Vector	V/Hz/Sensorless	V/Hz
Communication	Modbus RTU/CanOpen/DeviceNet	Profibus DP/DeviceNet/Ethernet IP/Modbus RTU	none
Configuration Software	ER SuperDrive Software	ER SuperDrive Software	none
Product Info page	4-4	4-5	4-6
Coding page	4-20	4-21	4-22

Soft Starters	Variable Speed Drive		
	 ERSSW03/04	 ERSSW05	 ERSSW06
Features			
Power Rating	37-1950kW/50-2600HP	0.55-55kW/0.74-75HP	22-475kW/30-75HP
Supply Voltage	220-575V	220-575V	220-575V
Display	Integral	Remote	Integral/Remote
Phases	3-Phase	3-Phase	3-Phase
Communication	Modbus RTU/Profibus DP/DeviceNet	RS232	Modbus RTU/Profibus DP/DeviceNet
Sizing/Configuration Software	ER SuperDrive Software & SDW Sizing Software	none	ER SuperDrive Software & SDW Sizing Software
Product Info page	4-8	4-9	4-10
Coding page	4-24	4-25	4-26

DC Drives	Variable Speed Drive		
	 ER-340/-680/-1200	 ER-3200i/3600XRi	 ER-PL/ER-PLX
Features			
Power Rating	0.55-1.8kW (at 180V armature voltage)	2.2-11kW (at 320V armature voltage)	15-265kW/15-225kW (at 460V armature voltage)
Supply Voltage	110/240V, 30/60V	240/2415V, 240/110V	110/240V, 30/60V
Display	none	none	Integral
Phases	1-Phase	1-Phase	3-Phase
Communication	none	none	Modbus TCP/Profibus DP
Armature Current	3.4-12.2A	4-48A	12-630A/12-530A
Configuration Software	ER-PL Pilot Software	ER-PL Pilot Software	ER-PL Pilot Software
Product Info page	4-12	4-13	4-14
Coding page	4-28	4-29	4-30

Software	 SuperDrive	 Soft Starter Sizing	 Configuration & Diagnostic
	ER	SDW	ER-PL PILOT
Product Info page	5-16	5-16	5-17
Coding page	—	—	—