











RoHS Compliant



PX-812

LP PCIe 1xRS232 POS 1A IDE

"SFRIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



Features

- 1 port RS232
- PCI Express x1, x4, x8 x16 lane slots socket
- 128 Byte Tx and 128 Byte Rx FIFOs
- Up to 921,600 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

Options



LP PCIe 1xRS232 POS 1A

Description

Low profile PCI Express Card providing one powered RS232 serial ports. Data transfer rates up to 921,600 baud rates and the 128 byte deep transmit and 128 byte receive FIFOS, coupled with 1Mbit/s line drivers deliver uncompromising performance on your PC. Up to 1 Amp selectable power provided through pins 1 and 9 to attached peripherals. The extra power necessary is supplied to the PCI express card directly from the PC power supply unit through a Parallel ATA PATA - or IDE power connector: a neat, clean and green solution. Drivers for Windows 32 bit and 64 bit Operating Systems including Windows 2000, XP, Server 2003, Vista, Server 2008, Windows 7 and Windows 8.


PCI Express is the latest standard in PC connectivity.

Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows 7 32 bit 64 bit Editions
- Windows Server 2008 32 bit 64 bit Editions
- Windows Vista 32 bit 64 bit editions
- Windows XP 32 bit 64 bit editions

As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.







ORDER Description LP PCIe 1xRS232 POS 1A IDE

Code PX-812



LP PCIe 1xRS232 POS 1A IDE

PX-812: Full Specification

PX-812: Full Specification		
Port	Ports	1 x RS232
Pin 1 DCD/12V/GND Pin 2 RXD Pin 3 TXD Pin 4 DTR Pin 5 GND Pin 6 DSR Pin 7 RTS Pin 8 CTS Pin 9 RI/12V/SV Pin 6 Pin 9 Pin 9 RI/12V/SV Pin 6 Pin 9 Pin 9 RI/12V/SV Pin 6 Pin 9 Pin 9	Connector FIFO size Operating Distance Cable	DB9 Connector - 9 Pin Male 128 RX FIFO + 128 TX FIFO EIA - RS232 Standard No Cable; Integrated Connector
Port Settings	Baud Rate	921,600
921,600 >>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>	Data Bits Parity Stop Bits Flow Control Tx/Rx Modes	5,6,7 or 8 Odd, Even, None, Mark or Space 1, 1.5 or 2 RTS/CTS, DSR/DTR, XON/XOFF Point to Point
Interface	OS Compatibility	Microsoft Windows 8 32 bit 64 bit Editions Microsoft Windows 7 32 bit 64 bit Editions Windows Server 2008 32 bit 64 bit Editions Windows Vista 32 bit 64 bit Editions Windows Server 2003 32 bit 64 bit Editions
	BUS	PCI Express x1, x4, x8 x16 lane slots
Approvals	Other Approvals	AEO C-TPAT WEEE ROHS EMC: CE
	Microsoft Approvals	Windows 7 32 bit 64 bit Editions Windows Server 2008 32 bit 64 bit editions Windows Vista 32 bit 64 bit editions Windows Server 2003 32 bit 64 bit editions Windows XP 32 bit 64 bit editions
General	PCB Layers	4
	Power Consumption	400mA @ 3.3V
	Weight	awaiting
	Size	awaiting
Box Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities
	Card	LP PCIe 1xRS232 POS 1A IDE
		No Cable; Integrated Connector
Product Support	Warranty	Lifetime (online registration required)
	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly staff who work in and alongside the Product Development Team
Additional	OEM option	Available for bulk buy OEM
Elektra O5 Europian Electronics Industry Awards	Made In	Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year"
WINNER Manufacturer of the Year Made in the UK	Customisable	Brainboxes operate a "Perfect Fit Custom Design" policy for volume users. More Info: sales@brainboxes.com

Other PCI Express Cards: 1 Port RS232 | 2 Port RS232 | 4 Port RS232 | 8 Port RS232 | 1 Port RS422/485 | 2 Port RS422/485 | 4 Port RS422/485 Other Brainboxes Ranges: PCI | Bluetooth Serial Adapter | Ethernet to Serial Adapter | PCMCIA Serial Card | ExpressCard Serial Adapter | USB to Serial