

# Wall & Rack Mount System

## Selection Guide



Model	BS-0996	BS-0981	BC-K201	BC-2602	BS-W025	
QR Code						
Pictures						
Mounting Type	1U Rack mount	1U Rack mount	2U Rack mount	4U Rack mount	Wall mount	
Dimensions (W x H x D) mm	482 x 45 x 250	482 x 45 x 250	428.2 x 88 x 310	430 x 177 x 330	277 x 136 x 316	
CPU Support	Intel® Core™ i5-7300U Core™ i3-7100U	Intel® Celeron® N3350: 2C, 2.4GHz Celeron® J3455: 4C, 1.5GHz	Intel® 10th Gen. Core™ / Pentium® / Celeron® / Xeon® W-1200 CPU	Intel® 9th / 8th Xeon®/ Core™ / Pentium® / Celeron® CPU (socket: LGA1151) (≤ 65W)	Intel® 7th / 6th Core™ / Pentium® / Celeron® CPU (socket: LGA1151)	
Chipset	--	--	Intel® W480E / Q470E / H420E	Intel® Q370 / H310 / C246	Intel® Q170 / H110 / C236	
Max. System Memory	16GB	16GB	128GB	64GB	32GB	
Drive Bay	1 x 2.5" SSD/HDD (SATA 3.0)	1 x 2.5" SSD/HDD (SATA 3.0)	2 x 2.5" SSD/HDD (SATA 3.0) or 1 x 3.5" HDD (SATA 3.0)	3.5" x 4 (SATA 3.0) 2.5" x 2 (optional)	2 x 2.5" SSD/HDD (SATA 3.0)	
Display	1 x HDMI 1 x DP	1 x DP	VGA 2 x DP	VGA 2 x DP	1 x VGA 1 x DVI-D	
Audio	Line Out	Line Out	Mic In / Line In / Line Out	Mic In / Line In / Line Out	Mic In / Line In / Line Out	
I / O  P O R T S	Serial Ports	2	4	2	6	2
	Parallel Port	--	--	--	1	--
	LAN	2	2	Dual (1G)	Dual (1G)	Dual (1G)
	USB	8	6	2 x USB 3.1 2 x USB 3.0 2 x USB 2.0	2 x USB 3.1 2 x USB 3.0 4 x USB 2.0	2 x USB 2.0 4 x USB 3.0
Expansion Slots	1 x mSATA 1 x mini PCIe	1 x mSATA 1 x PCIe (x1)	1 x PCIe (x16) 2 x PCIe (x4) 1 x PCIe (x1)	1 x PCIe (x16) 3 x PCIe (x4) 1 x PCIe (x1) 2 x PCI 1 x mini PCIe 1 x M.2 (2242) NVMe	1 x PCIe (x16) 2 x PCIe (x4) 1 x PCIe (x1)	
Power Requirement	DC In 12V/24V	DC In 12V	ATX	ATX	DC In 24V	
O.S. Support	Windows 10	Windows 10 / Windows 7	Windows 10	Windows 10	Windows 10 / Windows 7	
Certifications	CE, FCC	CE, FCC	CE, FCC	CE, FCC	CE, FCC	

\*All information contained in this document is subject to change without prior notice. Please log on [www.protech.com.tw](http://www.protech.com.tw) to acquire latest information.